

DOUBLE-SIDED PU MOUNTING TAPE

V2800

Product Description:

Normount V2800 is a high performance double-sided adhesive tape incorporating a black closed cell poly-urethane foam with a high shear acrylic adhesive on both sides. The combination of poly-urethane foam and acrylic adhesive enables use in applications where exceptional environmental performance is required.

To promote an adequate bond, the two surfaces must be clean and dry. Cleaning with a mixture of 50/50 water and I.P.A. has been found adequate.

The adhesive is pressure sensitive, we therefore recommend the application to be carried out at a minimum of 15c with as high a pressure as your process allows. A minimum of one bar pressure is required.

The standard thicknesses available are: 0.8mm 1.2mm 1.6mm

Technical information:

Internal code	V2800
St Gobain / Norton code	V2800
Colour	Black
Adhesive	Acrylic
Elongation at Break %	350
Tensile Strength (Kpa)	960
Water Absorption (%)	<5
180 Peel Adhsion (N/cm)	>12
Dynamic Shear (N/cn2)	>90
Service Temperature (C).	-40+100
ApplicationTemperature(C)	15-50

Please note: the above technical data is given as a guide and is based on recent test data obtained under laboratory conditions. Materials should be fully tested by the end user to establish the suitability of the product for the intended application.

Filcris Ltd

The Old Fire Station, Broadway, Bourn, Cambridge, CB3 7TE

Tel: 01954 718327

Fax: 01954 719908

Web: www.filcris.co.uk

Email: info@filcris.co.uk

Limited

FILCRIS